



Lift capacities calculated at attachment pivot point on stick (lbs).
No attachment on stick. Attachment weight must be subtracted.

REACH																HEIGHT
45'		40'		35'		30'		25'		20'		15'		10'		
Side	Front	Side	Front	Side	Front	Side	Front	Side	Front	Side	Front	Side	Front	Side	Front	
																45'
						*7,448	*7,448	*10,953	*10,953							40'
				*6,755	*6,755	*9,847	*9,847	*10,597	*10,597							35'
				*9,139	*9,139	*9,807	*9,807	*10,656	*10,656							30'
		7,158	*7,987	9,195	*9,212	*10,039	*10,039	*11,087	*11,087							25'
		7,020	*8,617	8,926	*9,444	*10,483	*10,483	*11,848	*11,848	*13,729	*13,729					20'
		6,807	*8,758	8,571	*9,768	11,011	*11,067	*12,848	*12,848	*15,485	*15,485	*19,839	*19,839	*28,483	*28,483	15'
5,329	*6,951	6,560	*8,908	8,175	*10,111	10,392	*11,683	13,628	*13,913	*17,394	*17,394	*23,651	*23,651			10'
5,194	*7,564	6,313	*8,996	7,786	*10,382	9,791	*12,200	12,677	*14,808	17,188	*18,933	*19,752	*19,752			5'
		6,100	*8,945	7,450	*10,491	9,284	*12,485	11,912	*15,308	16,022	*19,661	*13,218	*13,218	*5,776	*5,776	0'
		5,950	*8,658	7,201	*10,339	8,918	*12,421	11,399	*15,268	15,354	*19,447	*12,452	*12,452	*7,439	*7,439	-5'
		5,889	*8,000	7,064	*9,818	8,710	*11,909	11,133	*14,616	15,081	*18,351	*13,000	*13,000	*8,992	*8,992	-10'
				7,056	*8,779	8,665	*10,837	11,086	*13,290	15,098	*16,422	*13,954	*13,954	*10,302	*10,302	-15'
				*6,934	*6,934	8,790	*9,030	*11,173	*11,173	*13,604	*13,604	*15,134	*15,134			-20'
						*6,099	*6,099	*8,011	*8,011	*9,698	*9,698					-25'

Notes:

1. Do not attempt to lift or hold any load that exceeds these rated values at their specified load radii and heights.
2. The least stable position is over the side.
3. The operator should be fully acquainted with machine operation before operating the machine.
4. Lifting capacities assume a machine standing on level, firm and uniform supporting surface. Operator must make allowance for job conditions such as soft or uneven ground, out of level conditions, side loads, sudden stopping of loads, hazardous conditions, inexperienced personnel, etc.
5. The above theoretical ratings are based on calculations derived from standard O.E.M. lift charts. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping capacity. Rated loads marked with an asterisk (*) are limited by hydraulic lifting capacity. 5,960# additional counterweight installed.