



Lift capacities calculated at attachment pivot point on stick (lbs).
No attachment on stick. Attachment weight must be subtracted.

REACH																HEIGHT
45'		40'		35'		30'		25'		20'		15'		10'		
Side	Front	Side	Front	Side	Front	Side	Front	Side	Front	Side	Front	Side	Front	Side	Front	
								*10,805	*10,805							45'
						8,849	*9,678	*10,804	*10,804							40'
				6,366	*8,596	8,969	*9,474	*10,678	*10,678							35'
		4,512	*7,774	6,336	*8,534	8,778	*9,531	*10,864	*10,864							30'
		4,454	*7,744	6,102	*8,630	8,357	*9,773	*11,318	*11,318	*13,537	*13,537					25'
		4,256	*7,800	5,735	*8,817	7,760	*10,143	10,740	*11,981	*14,731	*14,731	*19,340	*19,340			20'
2,966	5,986	3,986	7,529	5,290	*9,039	7,052	*10,563	9,581	*12,735	13,521	*16,130					15'
2,807	5,817	3,693	7,215	4,824	9,059	6,326	*10,934	8,408	*13,395	11,453	*17,308					10'
2,651	5,653	3,417	6,920	4,396	8,596	5,679	10,902	7,421	*13,754	9,920	*17,557					5'
2,533	5,528	3,193	6,681	4,053	8,225	5,185	10,358	6,740	13,513	9,096	*14,019					0'
2,488	5,479	3,050	6,528	3,825	7,978	4,872	10,014	6,368	*13,081	8,791	*14,081	*7,332	*7,332			-5'
		3,012	6,487	3,727	7,871	4,739	9,869	6,250	*12,003	8,802	*14,452	*9,691	*9,691			-10'
		3,113	*5,372	3,771	*7,059	4,777	*8,670	6,338	*10,409	9,031	*12,212	*11,796	*11,796			-15'
				3,985	*5,280	4,987	*6,829	6,611	*8,211	*9,362	*9,362					-20'
						*4,103	*4,103									-25'

Notes:

1. Do not attempt to lift or hold any load that exceeds these rated values at their specified load radii and heights.
2. The least stable position is over the side.
3. The operator should be fully acquainted with machine operation before operating the machine.
4. Lifting capacities assume a machine standing on level, firm and uniform supporting surface. Operator must make allowance for job conditions such as soft or uneven ground, out of level conditions, side loads, sudden stopping of loads, hazardous conditions, inexperienced personnel, etc.
5. The above theoretical ratings are based on calculations derived from standard O.E.M. lift charts. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping capacity. Rated loads marked with an asterisk (*) are limited by hydraulic lifting capacity.