

## Trash Handling / Sorting

Builtrite Trash Handling/ Sorting Grapples are designed for handling, densifying and sorting all types of solid waste and C&D Debris. These grapples are ideal for use in waste transfer stations, C&D recycling vards and demolition sites, assisting with loading and sorting waste into truck trailers, roll-off containers or railroad cars. When fully closed, the lower edge of the grapple is angled down, allowing the operator to easily sort materials. The finest materials are used to provide maximum durability, exceptional performance and low maintenance.


- 360° continuous rotation on heavy duty bearing with high torque motor and high pressure hydraulic swivel.
- Large surface area when closed for optimal tamping performance.
- High tensile steel used throughout.

reducing your downtime. Key features include:

- Oversized, hardened cylinder and arm pivot pins with replaceable bushings.
- Bolt on replaceable wear edges.
- Easily accessible, yet well protected grease zerks.
- Made in U.S.A.

### **Options Include:**

- Can be offered in a hanging or wristing head configuration.
- Larger capacity arms (More width and depth).
- Can be mounted to Builtrite, Stationary Electric Material Handlers or excavators.





**Grapple Open Position** 




**Grapple Closed Position** 




# **Trash Handling / Sorting Grapple Specifications**


Model	*Weight		Height Closed		See Diagram		Overall Width Closed		See Diagram		Grapple Arm Width		Height @ Open		See Diagram		Full Open Inside Width		Full Open OutsideWidth	
			(A)		(B)		(C)		(D)		(E)		(F)		(G)		(H)		(I)	
	Lbs.	Kg.	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm
THS 20T	2,100	955	67	1,702	18	457	45	1,143	28	711	33	838	48	1,219	12	305	60	1,524	68	1,727
THS 24T	2,850	1,295	76	1,930	22	559	59	1,499	38	965	43	1,092	57	1,448	16	406	65	1,651	74	1,880


### Side View - Closed



Side View - Opened







Hydraulic Requirements								
	Flow GPM / LPM	Pressure PSL/Bar						
	GPIVI / LPIVI	PSI / Bai						
Open / Close	25 / 97	2-3,000 / 138-207						
Rotation	6 / 23	1,800 / 124						









NOTE: Northshore Manufacturing reserves the right to change specifications and prices without notice in order to follow its policy of constantly striving to manufacture a better product without incurring any liability to provide these new features on any units previously manufactured.

### Northshore Manufacturing, Inc.



