Augers • Chain Drive

The chain reduction drive units are designed for medium to heavy-duty applications, and are a very popular alternative to the planetary drive augers. Auger drives feature pre-stressed, fully adjustable reduction drives and the strongest connecting links available. Choose auger drive units and bits in 2-9/16" Round or 2" Hex output shafts. Complete units include the universal skid steer mount, top link, hoses, and flat-faced couplers. All bits sold separately.



| | 2-9/16" Round | | Model | Hyd. Req. (gpm/lpm) | Max. Auger Dia. (in/mm) | Speed (rpm) | Theo. Torque (lbs. ft/Nm) | Wt. (lbs) | Retail Price |
|---|---------------|---|--------|------------------------|----------------------------------|--------------|------------------------------|--------------|--------------|
| | Universal | | | | | | | | |
| | 503541 | 1200CL Auger Drive, Round - Complete | 1200CL | 10-20/38-76 | 30/762 | 106 @ 20 gpm | 1724/1547 @ 3000 psi | 360.0 | |
| * | 503542 | 1650CL Auger Drive, Round - Complete | 1650CL | 14-24/53-91 | 36/914 | 88 @ 24 gpm | 2478/2213 @ 3000 psi | 375.0 | |
| | 503543 | 2175CL Auger Drive, Round - Complete | 2175CL | 18-24/68-91 | 48/1219 | 73 @ 24 gpm | 2989/2703 @ 3000 psi | 430.0 | |
| | No Mount | | | | | | | | |
| | 50504135 | 500CL Auger Drive, Round - No Mount (Includes top link, 100" hoses and couplers) | 500CL | 6-14/23-53 | 18/457 | 132 @ 14 gpm | 980/882 @ 3000 psi | 156.0 | |
| | 503547 | 750CL Auger Drive, Round - No Mount (Includes top link, 100" hoses and couplers) | 750CL | 8-20/30-76 | 24/610 | 161 @ 20 gpm | 1118/1003 @ 3000 psi | 190.0 | |
| | 503548 | 1200CL Auger Drive, Round - No Mount (Includes top link, 100" hoses and couplers) | 1200CL | 10-20/38-76 | 30/762 | 106 @ 20 gpm | 1724/1547 @ 3000 psi | 228.0 | |
| | 503549 | 1650CL Auger Drive, Round - No Mount (Includes top link, 100" hoses and couplers) | 1650CL | 14-24/53-91 | 36/914 | 88 @ 24 gpm | 2478/2213 @ 3000 psi | 243.0 | |
| | 503550 | 2175CL Auger Drive, Round - No Mount (Includes top link, 100" hoses and couplers) | 2175CL | 18-24/68-91 | 48/1219 | 73 @ 24 gpm | 2989/2703 @ 3000 psi | 298.0 | |
| | 2" Hex | | Model | Hyd. Req. (gpm/lpm) | Max. Auger Dia. (in/mm) | Speed (rpm) | Theo. Torque (lbs. ft/Nm) | Wt. | Retail Price |
| | Universal | | | | | | | | |
| * | 503544 | 1200CLH Auger Drive, Hex - Complete | 1200CL | 10-20/38-76 | 30/762 | 106 @ 20 gpm | 1724/1547 @ 3000 psi | 375.0 | |
| | 503545 | 1650CLH Auger Drive, Hex - Complete | 1650CL | 14-24/53-91 | 36/914 | 88 @ 24 gpm | 2478/2213 @ 3000 psi | 390.0 | |
| | 503546 | 2175CLH Auger Drive, Hex - Complete | 2175CL | 18-24/68-91 | 48/1219 | 73 @ 24 gpm | 2989/2703 @ 3000 psi | 445.0 | |
| | No Mount | | | | | | | | |
| | 50504136 | 500CLH Auger Drive, Hex - No Mount (Includes top link, 100" hoses and couplers) | 500CL | 6-14/23-53 | 18/457 | 132 @ 14 gpm | 980/882 @ 3000 psi | 160.0 | |
| | 503551 | 750CLH Auger Drive, Hex - No Mount (Includes top link, 100" hoses and couplers) | 750CL | 8-20/30-76 | 24/610 | 161 @ 20 gpm | 1118/1003 @ 3000 psi | 205.0 | |
| | 503552 | 1200CLH Auger Drive, Hex - No Mount (Includes top link, 100" hoses and couplers) | 1200CL | 10-20/38-76 | 30/762 | 106 @ 20 gpm | 1724/1547 @ 3000 psi | 243.0 | |
| | 503553 | 1650CLH Auger Drive, Hex - No Mount (Includes top link, 100" hoses and couplers) | 1650CL | 14-24/53-91 | 36/914 | 88 @ 24 gpm | 2478/2213 @ 3000 psi | 258.0 | |
| | 503554 | 2175CLH Auger Drive, Hex - No Mount (Includes top link, 100" hoses and couplers) | 2175CL | 18-24/68-91 | 48/1219 | 73 @ 24 gpm | 2989/2703 @ 3000 psi | 313.0 | |