



For: Excavators/Material Handlers Type: Grapples

Applications: Automotive Recycling General Recycling

Features At-A-Glance

- Constructed of various high strength alloy steels.
- Hinge points utilize over-sized, hardened steel pins & bushings.
- Hydraulic cylinders, fittings & hoses are completely enclosed to prevent damage.
- Weld-on replaceable AR tips are standard.
- Raised ribs on leaf face to extend wear life.
- Available with 360° power rotation, or knock-around or fixed (no rotation).
- Four and five tine configurations available.
- Models OPG-50, OPG-75, OPG-100 and OPG-125 will go into a trailer or rail car for unloading.



COMPLETELY PROTECTED
Hydraulic Cylinder & Hoses
Covered in ALL POSITIONS
~ Nothing is Exposed ~

Model	Full Opening	Weight w/Rotation	Yard Capacity
OPG-50	65"	1,650 lbs	0.50
OPG-75	75"	3,200 lbs	0.75
OPG-100	85"	4,400 lbs	1.00
OPG-125	100"	4,600 lbs	1.25
OPG-150	113"	4,920 lbs	1.50
OPG-200	118"	5,710 lbs	2.00
OPG-300	144"	7,800 lbs	3.00



Quality Attachments Since 1978

PEMBERTON

