

Dust Fighter 20000X

Technical Specifications

- Electrical fan - 29.5 HP
- Water connection - 2" Cam Lock
- Nominal pressure - Min 29 Psi - Max 159 Psi
- Water consumption - 14 gallons/min 145 Psi
- Water filters - Yes
- Dimensions (LxWxH in) - 76"x67"x86"
- Electric - Three - phase/480V/60Hz
- Average water pressure - 87 Psi
- Coverage - 27,000-32,400 sq ft *no wind
- Type of water - potable/not potable
- Manual oscillation - 360 degrees
- Power oscillation - 325 degrees
- Weight - 1830 lbs

Standard Equipment

- This unit is an extreme condition version of the DF20000 with an IP67 control panel sealed against any moisture, dust, and corrosion. Also contains additional heater element for year-round use in any severe weather conditions
- Three - phase/480V/60Hz
- Pressure gauge
- 2 x Height adjustable stabilizers
- Control panel
- Complete with undercarriage and forklift pockets
- Integrated booster pumps to control the correct working pressure

Optional Equipment

- Automatic oscillation system managed from control panel; the range of work can cover from 0 to 300 degrees
- Pump for chemical additives
- Remote control to switch the Dust-Fighter on & off, pump on & off, & power oscillation (if present)
- 58KW-480V generator, or larger
- 850 - 1675 gallon water tank (custom designs & sizes on request)
- Steel skid base
- Heavy duty trailer



Dust Fighter Add-Ons

Water Tank



Generator



Trailer

