

INTIMIDATOR™ 18XP

18" Capacity Hand-Fed Chipper

The Intimidator 18XP is an amazing hydraulic-fed, drum-style chipper, **easily out-performing every other chipper in its class** while using approximately 30 percent less fuel per ton or cubic yard of chips produced. With a large 20-1/2" by 20-7/8" opening, a rugged 37" diameter chipping drum, a **powerful feed system** and **engine options up to 202 horsepower**, this overachieving chipper is ideal for tree removals and light land clearing. Self-propelled track undercarriages are optional.

DURABLE AND POWERFUL.

- **Aggressive feed systems** for unmatched pulling and compressing power
- **37" diameter drum** with impressive 20-1/2" wide throat opening
- **Gas or diesel engine options available**



Chip Limby Material With Limited Preparation

The Intimidator 18XP easily handles limby material with its chipper's large throat opening and Bandit's proven Slide Box Feed System. This system features powerful dual horizontal feed rollers 20" wide by 10-5/8" in diameter, powered by 32.3 CID hydraulic motors. The feed rollers are positioned within inches of the chipping knives, effectively controlling even the wildest trees and branches. This reduces trimming time and labor costs while increasing production.

Excels at Chipping Large Diameter Materials

The large 37" diameter drum allows much of the material to be chipped on the bottom half of the drum, with the grain of the wood like a disc-style chipper. The material is chipped using less energy and with less vibration, maximizing fuel economy and reducing maintenance. The large chipper opening and sloped infeed system makes it easy to feed large logs, branches and whole trees into the chipper.

Slide Box Feed System

This unique system allows the top feed wheel to move straight up and down with the flow and diameter of material passing through the feed system into the chipper. The slide box feed system provides direct down pressure for crushing material. Included within the slide box, is the patented spring tensioning system along with the hydraulic lift cylinder providing additional down pressure for unmatched pulling and compressing power making the unit easier to feed and more productive.

Significantly Less Maintenance

The Intimidator 18XP has a heavy, reinforced drum with internal baffles. The chipper drum and shaft should last the lifetime of the chipper and are backed by a five-year GUTS warranty. Rugged construction and heavy-duty components throughout the Intimidator 18XP help ensure long life and trouble-free performance. We realize what it costs when a chipper is down, and though we can't eliminate all downtime, we do our best to minimize it.

Higher Quality Chips Per Load

The Intimidator 18XP throws chips with more force due to the pocket design, the larger drum diameter, smooth transition, smooth discharges and the patented Power Slot. This means more chips per load and fewer trips to the dump site. It also means chips from a Bandit chipper have better uniformity compared to rival machines, commanding higher prices when sold and making them easier to dispose of.



Bandit

INDUSTRIES, INC.

6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178

FIND US ONLINE



WWW.BANDITCHIPPERS.COM

Intimidator™ 18XP

18" capacity drum-style chipper



Safety Features

- **Rope/Line Shear Device** (standard)
Provides an improved chance that rope or lines inadvertently entering the chipper may be cut.
- **Last Chance Cables** (standard)
Stops/reverses the feed wheel when pulled in case of an emergency.
- **Operator Safety Control Bar** (standard)
Wraps around three sides of the infeed chute and controls the direction of the feed wheels.
- **Wood Pusher Paddle** (standard)
Used to feed small wood debris into the chipper.
- **Chipper Hood Pin w/Padlock** (standard)
Prevents unauthorized access to the disc or drum.
- **Chipper Hood Engine Disable Plug** (standard)
Prevents engine from being started without the hood pin in place.
- **Feed Wheel Engage** (option)
Requires operators to control feed wheel operation via foot pedal.
- **Hydraulic Bottom Bump Bar** (option)
Stops feed wheels via mechanical connection when bumped, diverting hydraulic power away from the feed wheels.

The Bandit Backbone™ Support

The Bandit Backbone™ is Bandit's commitment to customer service and support. It's always been a cornerstone of Bandit's philosophy, and today that backbone is stronger than ever. If you own a Bandit track carrier – regardless the age, hours, or warranty status – the Bandit Backbone is here to support you.



Popular Options



Gas Engine

Get a powerful 165 horsepower GM gasoline engine to power the Model 18XP.



Self-Propelled

Available with a track undercarriage, the Intimidator 18XP can be taken directly to the trees.



Hydraulic Winch

This useful option enables the operator to pull large material to the chipper with ease.

Intimidator™ 18XP Specifications

ENGINES

TOWABLE:

- GM 130 or 165 HP Gas
- CAT or Perkins 122.5 HP Tier 4 Final
- CAT or Perkins 147 HP Tier 4 Final
- CAT or Perkins 174 HP Tier 4 Final
- CAT or Perkins 202 HP Tier 4 Final
- John Deere 139 HP Tier 4 Final
- John Deere 173 HP Tier 4 Final
- John Deere 200 HP Tier 4 Final

TIER 3 DIESEL ENGINE OPTIONS (EXPORT ONLY)

- CAT or Perkins 122.5 HP Tier 4 Final
- CAT 142 HP Tier 3
- CAT 213 HP Tier 3
- John Deere 140 HP Tier 3
- CAT or Perkins 173.7 HP Tier 3

TRACK:

- CAT/Perkins 174 HP Tier 4 Final

TIER 3 DIESEL ENGINE OPTIONS (EXPORT ONLY)

- CAT 142 HP Tier 3
- John Deere 140 HP Tier 3
- CAT 213 HP Tier 3

UNDERCARRIAGES

TOWABLE:

AXLE - Single 10,000 or 12,000 lb. electric brake axles
TIRES - (2) 215/75R 16" tires mounted on 8-bolt heavy-duty gray rims

TRACK:

RUBBER TRACK - 305 DCR rubber track undercarriage
STEEL TRACK - Caterpillar 305CR (400MM, triple grouser)

MEASUREMENTS:

| | TOWABLE: | TRACK: |
|-----------------------------------|-----------|------------|
| Length: (Infeed Closed) | 16' | 12' 6" |
| Length: (Infeed Open) | 18' 1" | 14' 5" |
| Width: | 7' 4" | 8' 6" |
| Height: | 8' 6" | 9' 3" |
| Weight: | 9,000 lbs | 12,500 lbs |
| Fuel Tank: | 30 gal | 50 gal |
| Hyd. Tank: | 12 gal | 50 gal |

OTHER SPECIFICATIONS:

| | |
|--------------------------------|---|
| Capacity: | 18" |
| Throat Opening: | 20-1/2" x 20-7/8" |
| Drum: | 37" diameter x 22" wide (3/8" Thick) |
| RPM: | 1,080 |
| Feed System: | Slide box 20-1/2" x 18" |
| Adjustable Springs: | 2 - 21" |
| Horizontal feed wheels: | 20" wide x 10-5/8" diameter |
| Displacement (CID): | 32.3 |
| Hydraulic Motors: | 2 |
| Discharge: | Standard w/ 360° swivel |
| Deflector: | 3-Position Manual |
| Hitch: | 3 Position - 2-1/2" Pintle |
| Frame: | 3/16" x 2" x 6" main frame rectangular tubing with a 3/8" x 3" x 6" tongue |
| Fenders: | Preformed 12 gauge aluminum tread brite fenders with mud shields |
| Tongue Jack: | 8,000 pound "Bulldog" tongue jack, adjustable for height with 15" travel capacity and stationary foot pad |

Standard & Custom Colors Available

Choose from six standard colors, or select a custom color to match your fleet.

