

Specifications

Spec.	Fork Grapple
	
Width	50" (1270 mm)
Length	48" (1219 mm)
Opening Height	66" (1676 mm)
Weight	700 lbs. (317 kg)
SSL Auxiliary Hyd. Circuits Required	1
Hyd. Relief Setting	3000 PSI (207 bar)

Spec.	X-treme Grapple Bucket					
						
Width	66" (1676mm)	72" (1829mm)	78" (1981mm)	84" (2134mm)	96" (2348mm)	
Length	39" (990mm)					
Opening Height)	45" (1143mm)					
Weight	1000 lbs. (454 kg)	1050 lbs. (476 kg)	1100 lbs. (499 kg)	1160 lbs. (526 kg)	1260 lbs. (5715 kg)	
SSL Auxiliary Hyd. Circuits Required	1					
Hyd. Relief Setting	3000 PSI (207 bar)					

Spec.	Heavy Duty Grapple Bucket					
						
Width	63" (1600mm)	66" (1676mm)	72" (1829mm)	78" (1981mm)	81" (2057mm)	
Length	34" (863mm)					
Opening Height	38.6" (980mm)					
Weight	750 lbs. (340 kg)	800 lbs. (363 kg)	850 lbs. (386 kg)	875 lbs. (397 kg)	925 lbs. (420 kg)	
SSL Auxiliary Hyd. Circuits Required	1					
Hyd. Relief Setting	3000 PSI (207 bar)					

Spec.	Standard Duty Grapple Bucket	
		
Width	63" (1600mm)	72" (1829mm)
Length	34" (863mm)	
Opening Height	38.6"(980mm)	
Weight	500 lbs. (227 kg)	525 lbs. (238 kg)
SSL Auxiliary Hyd. Circuits Required	1	
Hyd. Relief Setting	3000 PSI (207 bar)	


Spec.	Light Duty Grapple Bucket		
			
Width	60" (1524mm)	63" (1600mm)	72" (1829mm)
Length	34" (863mm)		
Opening Height	38.6"(980mm)		
Weight			
SSL Auxiliary Hyd. Circuits Required	1		
Hyd. Relief Setting	3000 PSI (207 bar)		

Spec.	X-treme Grapple Rake			
				
Width	63" (1600mm)	72" (1829mm)	84" (2134mm)	96" (2348mm)
Length	21" (533mm)			
Opening Height	58"(1473mm)			
Weight	820 lbs. (372 kg)	900 lbs. (408 kg)	1050 lbs. (476 kg)	1150 lbs. (522 kg)
SSL Auxiliary Hyd. Circuits Required	1			
Hyd. Relief Setting	3000 PSI (207 bar)			
	Standard Duty Grapple Rake			

			
Width	63" (1600mm)	66" (1676mm)	72" (1829mm)
Length	21" (533mm)		
Opening Height	58"(1473mm)		
Weight	700 lbs. (318 kg)	725 lbs. (329 kg)	750 lbs. (340 kg)
SSL Auxiliary Hyd. Circuits Required	1		
Hyd. Relief Setting	3000 PSI (207 bar)		
Spec.	Rock Grapple Bucket		
			
Width	63" (1600mm)	72" (1829mm)	81" (2057mm)
Length	34" (863mm)		
Opening Height	38.6"(980mm)		
Weight	700 lbs. (318 kg)	725 lbs. (329 kg)	750 lbs. (340 kg)
SSL Auxiliary Hyd. Circuits Required	1		
Hyd. Relief Setting	3000 PSI (207 bar)		

Spec.	X-treme Root Grapple					
						
Width	63" (1600mm)	66" (1676mm)	72" (1829mm)	78" (1981mm)	81" (2057mm)	84" (2134mm)
Length	42" (1066mm)					
Opening Height	42.75"(1085mm)					
Weight	915 lbs. (415 kg)	950 lbs. (431 kg)	975 lbs. (442 kg)	1000 lbs. (454 kg)	1025 lbs. (465 kg)	1050 lbs. (476 kg)
Hyd. Circuits Required	1					
Hyd. Relief Setting	3000 PSI (207 bar)					

	Heavy Duty Root Grapple
--	--------------------------------

					
Width	63" (1600mm)	66" (1676mm)	72" (1829mm)	78" (1981mm)	81" (2057mm)
Length	38.25" (972mm)				
Opening Height	35.3"(897mm)				
Weight	700 lbs. (318 kg)	725 lbs. (329 kg)	750 lbs. (340 kg)	770 lbs. (349 kg)	800 lbs. (363 kg)
SSL Auxiliary Hyd. Circuits Required	1				
Hyd. Relief Setting	3000 PSI (207 bar)				

Spec.	Standard Duty Grapple Bucket		
			
Width	63" (1600mm)	66" (1676mm)	72" (1829mm)
Length	38.25" (972mm)		
Opening Height	35.3"(897mm)		
Weight	600 lbs. (272 kg).	625 lbs. (284 kg)	650 lbs. (295 kg)
SSL Auxiliary Hyd. Circuits Required	1		
Hyd. Relief Setting	3000 PSI (207 bar)		

Spec.	Single Cylinder Light Duty Grapple Bucket		
			
Width	60" (1524mm)	66" (1676mm)	72" (1829mm)
Length	35.25" (895mm)		
Opening Height	31.3"(980mm)		
Weight			
SSL Auxiliary Hyd. Circuits Required	1		
Hyd. Relief Setting	3000 PSI (207 bar)		

	X-treme Tine Grapple
--	-----------------------------

						
Width	63" (1600mm)	66" (1676mm)	72" (1829mm)	78" (1981mm)	81" (2057mm)	84" (2134mm)
Length	33.5" (851mm)					
Opening Height	38."(978mm)					
Weight	975 lbs. (415 kg)	1000 lbs. (431 kg)	1050 lbs. (442 kg)	1100 lbs. (454 kg)	1125 lbs. (465 kg)	1150 lbs. (476 kg)
SSL Auxiliary Hyd. Circuits Required	1					
Hyd. Relief Setting	3000 PSI (207 bar)					

Spec.	Light Duty Grapple Bucket		
			
Width	60" (1524mm)	63" (1600mm)	72" (1829mm)
Length	34" (863mm)		
Opening Height	38.6"(980mm)		
Weight			
SSL Auxiliary Hyd. Circuits Required	1		
Hyd. Relief Setting	3000 PSI (207 bar)		

Spec.	Stump Grapple
	
Width	45.5" (1156 mm)
Length	34.4" (874 mm)
Opening Height	45.3"(1151 mm)
Weight	575 lbs. (261 kg)
SSL Auxiliary Hyd. Circuits Required	1
Hyd. Relief Setting	3000 PSI (207 bar)

Spec.	Manure Fork Grapple		
			
Width	60" (1524mm)	66" (1676mm)	72" (1829mm)
Length	30.5" (775mm)		
Opening Height	32" (813mm)		
Weight	404 lbs. (183 kg)	470 lbs. (213 kg)	527 lbs. (239 kg)
SSL Auxiliary Hyd. Circuits Required	1		
Hyd. Relief Setting	3000 PSI (207 bar)		