



Excavator Attachments

Reach Your Excavator's Potential

**Bull Hog® Mulchers • Stump Grinders • Tree Shears
Power Packs • Log Jaw Wood Splitter**



Bull Hog

Excavator



BH80EXC

Bull Hog Excavator Mulchers for 7 - 45 Ton Excavators
 Power Pack Not Required
 Three Rotor Choices - FGT, HDT or DCR
 Four Tool Choices per Rotor
 Fixed Displacement or Variable Displacement Motors
 Priority Valve Recommended for Some Excavators



BH62EXC



Shown with FGT Rotor

CEM36 WITH
 OPTIONAL THUMB RECEIVER

FEATURES

- Heavy or Severe Duty Models
- Low Maintenance Design
- Exceptional Tool Life
- Stout Rotor and Body
- The most durable mulcher on the market!

HDT ROTOR SYSTEM TOOL CHOICES:



Double Carbide



Stone Tool



Single Carbide



Chipper Knife

FGT ROTOR SYSTEM TOOL CHOICES:



Double Carbide



Severe Duty



Stone Tool



Samurai Knife

TYPE	MODEL	OVERALL WIDTH	WORKING WIDTH	APPROX WEIGHT	APPROX FLOW RANGE	COMMON EXC SIZE (METRIC TON)
Heavy Duty	CEM36	52"	36"	1,300 lbs	17-30 gpm	7-15 ton
Heavy Duty	BH47EXC	50"	37"	2,200 lbs*	27-45 gpm	12-20 ton
Heavy Duty	BH62EXC	62"	50"	2,500 lbs*	27-45 gpm	12-20 ton
Severe Duty	BH40EXC	51"	36"	3,000 lbs*	30-105 gpm	15-30 ton
Severe Duty	BH80EXC	71"	56"	4,000 lbs*	38-105 gpm	20-45 ton
Severe Duty	BH200EXC	77"	59"	4,400 lbs*	40-180 gpm	20-45 ton

CEM36 listed weight includes typical mount.

CEM36 comes standard with a variable displacement hydraulic motor.

All other models can be equipped with variable displacement or fixed displacement hydraulic motors.

*Weights listed for EXC models will vary based on hydraulic motor choice and options & do not include weight of the mount.

BHP

Power Packs

FEATURES

- Equipped with Fecon Power Management®
- Dramatically Improves Engine Response/Recovery
- Sustained Peak Grinding Power
- Reduced Fuel Consumption
- Optimized Operator Feedback
- Limited Stalling
- Quicker Recovery
- Maximized Productivity

Mulch Brush, Branches, Slash, Standing and Fallen Trees, Root Balls and Stumps faster and more effectively than before!



Bull Hog Excavator Mulchers are most often powered by the excavator's hydraulic system. However, when absolute maximum productivity is required a Bull Hog Power Pack provides the ultimate solution.

COMMON EXC SIZE	MODEL	ENGINE	BULL HOG	STUMP HOG
12 Ton & Higher	BHP170	170hp Cummins	BH62EXC/BH40EXC	SH360-61
20 Ton & Higher	BHP250	250hp CAT or JD	BH80EXC/BH200EXC	SH360-100

APPLICATIONS

- R.O.W.
- Land Clearing
- Forestry Applications
- Orchard Clean-up and Removal
- Prairie and Wetland Restoration
- Agricultural Preparation and Land Development
- Invasive Species - Beetle Kill and Noxious Weeds
- Wild Fire Urban Interface Mechanical Fuel Treatments



Excavator Bull Hog®

Heavy Duty

- 7-20 Ton Excavators
- CEM36, BH47EXC and BH62EXC
- Variable Displacement Motor Options

SEVERE Duty

- **3/4"** Steel Body Construction
- BH40EXC, BH80EXC and BH200EXC
- 15 - 45 Ton Excavators
- SEVERE Duty Bearings
- Variable Displacement Motor Options

Mounts

- Quick Attach or Pin-On
- Easily Change Mounts for Different Excavators with the Bolt-on Interface

Rotor Exposure

- Cut Through Standing Trees
- Mulch Slash Piles
- Grind to the Surface





fecon.com
sales@fecon.com
+1 513 696 4430

Log Jaw™ Wood Splitter

Downsize wood waste with Fecon's Log Jaw™ attachment for excavator models up to 16 ton. The Log Jaw will rip apart long, large diameter logs and stumps into manageable pieces for chipping, grinding and firewood processing.

LJ40EXC - Technical Specifications	
Height (tips to mount)	80" / 2032 mm
Weight (with mount)	995 lbs / 452 kg
Jaw Opening (tip to tip)	40.25" / 1022 mm
Hydraulic Cylinder	5" x 24" w/ 3" Rod 127 mm x 610 mm w/ 76 mm Rod
Rotator	360° Rotation



Stump Hogs

- Just 15 Tools with single bolt fastening
- Three tool choices for lower operating costs
- Unlimited swing, reach and depth for the hard to reach stumps that cannot be safely accessed with a traditional stumper
- Wheel supported on both sides
- Interchangeable with Fecon Mulcher
- Guard (removable) for working in sensitive areas.
- Polychain belt drive
- Bolt on mount custom to excavator with pin-on or quick attach options

Technical Specifications		
Weight	2600 lbs.	
Wheel Diameter	36"	
Model	Excavator Size	Hydraulic Flow
SH360-45	20 - 30 ton	40-55 gpm
SH360-61	33 ton and higher or BHP170 on 12 ton or higher	60-80 gpm
SH360-100	BHP250	100 - 120 gpm



Tree Shears

- Fecon offers models for excavators 8 ton and up. Requires as little as 20 gpm of Low Flow Hydraulics.
- Great for reaching up and down slopes and areas that are otherwise inaccessible.
- Provided with Fecon "H" mounting bracket and bolt-on hanger bracket sized to the Excavator.
- AR400 Shear knives.

General	FBS1200EXC	FBS1400EXC	FBS1500EXC	FBS1600EXC
Height	64"	64"	70"	70"
Width	50"	48"	64"	62"
Depth	40"	42"	46"	67"
Weight	1450 lbs.	2000 lbs.	2100 lbs.	3700 lbs.
Cutting Capacity Diameter	12"	14"	15"	16"
Grabber Arm	2	1	2	1
Accumulator Arm	1	1	1	1
Knife Action	Double	Single	Double	Single
Excavator Size	8-16 Ton	12-18 Ton	12-18 Ton	20 Ton Max



• Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
 • Always insure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection) meet your job safety requirements.
 • Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
 • Weights may vary based on options.
 • Safety Is The Responsibility Of The Operator. • Specifications subject to change without notice.
 • Pictures may contain optional accessories. • Photographs may have been altered for marketing purposes.



GS-30F-0019S