



# T-REX 300/300mt



**JARRAFF**  
By *Pinoth*

## WHAT ARE PEOPLE SAYING ABOUT THE NEW T-REX 300/300mt?

- The T-REX 300/300mt can do a variety of different tasks.
- Using this single machine now does what three machines were doing before, game changer!
- The universal front attachment options have saved us time, money, and hassle.

## TIME IS MONEY, AND WITH THE T-REX 300/300mt, YOU CAN DO SO MUCH MORE WITH LESS.

Use your favorite machine in multiple applications. From brush cutting to stump grinding, the T-REX 300/300mt can do it all. The newly redesigned T-REX 300/300mt keeps your favorite features like high power density, cabin comfort and safety, but now, the new addition of the universal front coupler means that you can use your T-REX 300/300mt with other attachments. Everyone knows that time is money, and the T-REX 300/300mt allows dealers, rental houses, and operators to do more than just mulching.



UNIVERSAL HYDRAULIC QUICK COUPLER



MORE CAPABILITIES



MORE WORK



MORE VALUE

### ATTACHMENTS MADE SIMPLE

All machines are outfitted with a JRB416 universal hydraulic quick coupler, so mounting attachments is as easy as a push of a button.

### POWER DENSITY

The machine is 20% smaller than others in its class yet offers more power. This increases functionality with reduced fuel consumption and lower costs.

### ROAD WIDTH

Machine dimensions (8'4") fit the legal road limit, eliminating the need for special permits when transporting.

### CHOOSE WHEELS OR TRACKS

Both models include hydrostatic all-time 4-wheel drive and an articulated undercarriage to help you get anywhere the jobs take you.

### SAFETY AND COMFORT IN THE CABIN

ROPS and FOPS certified, climate controlled with an ergonomic joystick and touch screen control center help the operator stay safe and feel comfortable so they can keep their focus on the job.




### FLEET READY

T-REX 300/300mt are built to last so you can count on the machine to run when you need it most. This helps avoid downtime, reduce maintenance intervals and cut down on expenses.

### SERVICE AND SUPPORT YOU CAN COUNT ON

Manufactured at the St. Peter MN facility, the service network you trust will continue long past the initial purchase.

## TECHNICAL SPECIFICATIONS



	WHEEL	QUAD TRACK
<b>PERFORMANCE</b>		
Lift Height	15 ft 8 in	16 ft 2 in
Tipping Limit	19,000 lbs	
Breakout Force	10,100 lbf	
Auxiliary Hydraulics	(2) Open Loop 3000psi @ 26gpm - Quick Disconnect (Adjustable Flow) (1) Closed Loop 5800psi @ 74gpm - Quick Disconnect (On/Off)	
Coupler	JRB 416 - Hydraulically Actuated	
Max Travel Speed	14 mph	9 mph
<b>SPECIFICATIONS</b>		
Weight*	26,300 lbs	32,500 lbs
Length	24ft	
Width	8 ft / 6 in	
Height	9 ft 11 in	10 ft 4 in
<b>GROUND PRESSURE</b>	9.3 psi	5.5 psi
<b>ENGINE</b>		
Make / Model / Type	Cummins 6.7L Diesel	
Emission Level	EPA Tier 4 Final	
Max Power Output	260 HP @ 2200 rpm	
<b>MAXIMUM GRADEABILITY</b>	25° / 46%	

\*w/ Prinoth Mulchhead



**JARRAFF INDUSTRIES LLC**  
1730 N Gault Street, St Peter, MN 56082, USA

507-934-8688 | [jarraff.com](http://jarraff.com)