

# MHP


### **MOBILE HYDRAULIC PULVERIZERS**

#### **DEMOLITION SOLUTIONS**

Designed for high efficiency secondary demolition and concrete recycling, the LaBounty Mobile Hydraulic Pulverizers (MHP) offers industry-leading power-to-weight and large jaw capacities. The all-new MHP design has been optimized to pick-up, crush, and separate rebar from concrete faster than ever before thanks to high-tip forces, a large jaw, and fast cycle times.

## **MOBILE HYDRAULIC PULVERIZERS**

The LaBounty MHP's unique shape makes it extremely versatile for use on the ground, facilitating demolition of walls and vertical cement structures, pavement, and concrete slabs.



#### **SPECIFICATION TABLE**

Model	Weight*		Jaw Opening		Jaw Width		Reach**		Min Excavator Weight - 3rd Member***	
	lbs	kg	in	mm	in	mm	ft	m	lbs	mTons
MHP 80	1,750	800	20.9	530	14.4	370	5.2	1.6	13,200	6
MHP 150	3,000	1,400	27.6	700	18.1	460	6.1	1.8	28,600	13
MHP 220	4,680	2,100	32.5	830	21.3	540	7.1	2.2	39,600	18
MHP 300	6,330	2,900	34.3	870	26.4	670	7.4	2.3	55,000	25
MHP 390	7,740	3,500	37.4	950	29.1	740	7.9	2.4	72,600	33
MHP 550	10,680	4,800	44.5	1130	30.0	760	8.9	2.7	99,000	45
MHP 750	15,050	6,800	49.2	1250	31.5	800	9.8	3.0	143,000	65

<sup>\*</sup>Weight includes standard excavator mounting bracket. Attachment weight may vary depending on mounting configuration as well as options.

LaBounty reserves the right to improve, update, or change the product specifications, appearance, or functional attributes without notice.







<sup>\*\*</sup> Reach is measured from the attachment mounting pivot (boom or stick) forward to the end of the jaw.

<sup>\*\*\*</sup> Excavator weight range should be used as a guide only, all mounting configurations must be preapproved by LaBounty.