



LABOUNTY

www.stanleyinfrastructure.com/brands/labounty

MRX SERIES

MULTI-JAW DEMOLITION TOOL

DEMOLITION SOLUTIONS

The MRX takes versatility to the next level with its three interchangeable jaws - a concrete pulverizer, concrete cracker, and shear - making it the ideal solution for primary and secondary demolition needs. Additionally, the MRX boasts a short center of gravity and 360-degree rotation, providing optimal maneuverability.

MULTI-JAW DEMOLITION TOOL

- **Jaw Interchange Visibility** for easier swapping
- **Improved Handling and Wear-Protection** on jaws
- **Reverse Cylinder** with internal hydraulic lines protects components from debris
- **Dual Rotation Motors** for superior control and reliability
- **Easy to Change Teeth** to minimize downtime
- **Cutting Blade** to remove nuisance rebar

CHOOSING THE RIGHT JAW - 5 MINUTE JAW CHANGES

CONCRETE PULVERIZER - CP



CONCRETE CRACKER - CC



SHEAR JAW - SH



SPECIFICATION TABLE

Model	Jaw	Weight (with jaw)*		Jaw Opening		Jaw Depth		Reach**		Min Excavator Weight - 3rd Member***	
		lbs	kg	in	mm	in	mm	ft	m	lbs	mTons
MRX 70	Shear (SH)	1,670	760	9.8	250	12.8	330	5.2	1.6	15,000	7
	Concrete Pulverizer (CP)	1,760	800	20.9	530	20.1	510	5.6	1.7	15,000	7
	Concrete Cracking (CC)	1,760	800	20.7	530	19.3	490	5.7	1.7	15,000	7
MRX 100	Shear (SH)	2,350	1,070	12.6	320	15.4	390	6.1	1.9	20,000	9
	Concrete Pulverizer (CP)	2,460	1,120	26.0	660	24.0	610	6.6	2.0	20,000	9
	Concrete Cracking (CC)	2,520	1,140	23.6	600	24.0	610	6.7	2.0	20,000	9
MRX 130	Shear (SH)	3,330	1,510	15.7	400	17.7	450	6.6	2.0	29,000	13
	Concrete Pulverizer (CP)	3,450	1,570	28.3	720	24.8	630	7.1	2.2	29,000	13
	Concrete Cracking (CC)	3,320	1,510	29.1	740	28.0	710	7.3	2.2	29,000	13
MRX 180	Shear (SH)	4,520	2,050	17.0	430	18.4	470	7.5	2.3	40,000	18
	Concrete Pulverizer (CP)	4,740	2,150	28.2	720	26.0	660	7.9	2.4	40,000	18
	Concrete Cracking (CC)	4,620	2,100	29.4	750	27.3	690	8.3	2.5	40,000	18
MRX 220	Shear (SH)	6,070	2,800	19.1	480	20.1	510	8.3	2.5	48,000	22
	Concrete Pulverizer (CP)	6,270	2,800	32.7	830	29.8	760	8.8	2.7	48,000	22
	Concrete Cracking (CC)	6,180	2,800	33.1	840	31.3	790	9.1	2.8	48,000	22
MRX 260	Shear (SH)	8,220	3,700	19.5	500	22.4	570	8.9	2.7	57,000	26
	Concrete Pulverizer (CP)	8,600	3,900	33.1	840	31.5	800	9.4	2.9	57,000	26
	Concrete Cracking (CC)	8,290	3,800	33.4	820	31.9	810	9.4	2.9	57,000	26
MRX 360	Shear (SH)	9,270	4,200	21.1	540	22.2	570	8.8	2.7	79,000	36
	Concrete Pulverizer (CP)	10,100	4,600	37.4	950	36.1	920	9.5	2.9	79,000	36
	Concrete Cracking (CC)	9,630	4,400	35.5	900	35.5	900	9.7	3.0	79,000	36
MRX 500	Shear (SH)	13,600	6,170	22.6	570	26.0	660	9.8	3.0	117,000	53
	Concrete Pulverizer (CP)	15,030	6,820	43.3	1,100	40.6	1,030	10.8	3.3	117,000	53
	Concrete Cracking (CC)	14,610	6,630	45.3	1,150	42.1	1,070	11.0	3.4	117,000	53
MRX 750	Shear (SH)	19,820	9,000	27.6	700	30.0	760	11.1	3.4	165,000	75
	Concrete Pulverizer (CP)	21,320	9,680	46.3	1,180	43.4	1,100	11.8	3.6	165,000	75
	Concrete Cracking (CC)	20,670	9,380	46.3	1,180	45.7	1,160	11.8	3.6	165,500	75

*Weight includes standard excavator mounting bracket. Attachment weight may vary depending on mounting configuration as well as options.

** Reach is measured from the attachment mounting pivot (boom or stick) forward to the end of the jaw.

*** Excavator weight range is a guide only. 2nd member configurations at or near min/max excavator weight and all 3rd member configurations must be preapproved by LaBounty. Quick couplers, short swing machines, long arms all impact carrier size recommendation.

LaBounty reserves the right to improve, update, or change the product specifications, appearance, or functional attributes without notice.