

MKT HYDRAULIC AUGER SYSTEMS

- Fixed and variable torque models
- High output & torque speeds
- Remote pendant controls for all operations
- Lead mounted tie-back installation systems
- Pre-drilling, augercast, drilling out driven pip
- Uncomplicated hydraulic circuitry
- Manufactured & assembled in St. Louis, MO facility
- Enclosed power units
- Custom auger systems



MKT

HA-18A/HP-185T3 AND HVA-40/HP 365DV HYDRAULIC AUGER

HA-18A and HVA-40 Hydraulic Auger Specifications				
AUGER	HA-18A		HVA-40	
Output Torque	18,000 ft-lbs		14,000 to 40,000 ft-lbs	
Output Speed	0-45 RPM		33 to 100 RPM	
Max. Line Pull/Crowd	12 Tons	106kN	17 tons	151kN
Lead Size	8" x 20"		8" x 26"	
Length	32 in.	813 mm	30 in.	762 mm
Width	20 1/2 in.	521 mm	26 in.	660 mm
Height	66 in.	1,676 mm	60 in.	1,592 kg
Weight	2,250 lbs.	1,023 kg.	3,500 lbs.	1,592 kg
Hose Bundle Length	100 ft.	30 m	100 ft.	30 m
POWER UNIT				
Engine HP	185 hp	138 kW	365 hp	272 kW
Operating Speed	2,100 RPM		2,250 RPM	
Hyd. Flow	82 gpm	310 lpm	90 gpm	342 lpm
Hyd. Pressure	3,500 psi	341 bar	5,000 psi	345 bar
Length	120 in.	3048 mm	132 in.	3,353 mm
Width	47 in.	1,193 mm	48 in.	1,219 mm
Height	66 in.	1,676 mm	84 in.	2,134 mm
Weight	5,750 lbs	2,616 kg	9,500 lbs	4,322 kg

Distributed by:



MKT Manufacturing, Inc.

1198 Pershall Rd • St. Louis, MO 63137
phone (314) 388.2254 • fax (314) 388.1218
www.MKTPILEMAN.com