

MKT SIDE CLAMP VIBRATORY DRIVERS/EXTRACTORS



- Excavator mount or crane hung
- Removable side-clamp & Rototilt attachments
- Power w/ excavator or MKT hydraulic power unit
- Operate with remote pendant, Remtron wireless remote, or joystick controls
- Rotational, side-to-side, fore / aft capabilities for pile plumbing & placement
- Same internal design as classic MKT V-2 & V-5 series
- Low headroom applications
- Efficient for compact jobsites & high-production jobs
- 24 hr parts & service support



MKT

V-2ESC/HP-85T3 and V-5ESC/HP-185T3 VIBRATORY DRIVER/EXTRACTOR

V-2ESC/HP-85T3 and V-5ESC/HP-185T3 Specifications

HAMMER	V-2ESC		V-5ESC	
Driving Force	25 tons	223 kN	53 tons	472 kN
Frequency	1,800 CPM		1,700 CPM	
Eccentric Moment	550 in-lbs	635 kg-cm	1,300 in-lbs	1,500 kg-cm
Amplitude	.75 in.	19 mm	1 in.	25.4 mm
Clamping Force	16 tons	145 kN	62 tons	550 kN
Max. Line Pull Free Hanging	16 tons	145 Kn	30 tons	267 kN
Max. Line Pull W/ Side Clamp	8 tons	72 kN	15 tons	134 kN
Max. Crowd W/ Side Clamp	8 tons	72 kN	15 tons	134 kN
Height of Hammer	48 in.	1,219 mm	78 in.	1,981 mm
Throat Width	14 ¾ in.	374 mm	13 in.	330 mm
Shipping Width	57 in.	1,447 mm	85 in.	2,158 mm
Weight as shown	5,300 lbs	2,405 kg	10,000 lbs	4,550 kg
Free Hanging Weight	3,300 lbs	1,497 kg	6,200 lbs	2,821 kg
Hose Bundle Length	100 ft.	30 m	100 ft.	30 m

POWER UNIT	HP-85T3		HP-185T3	
Engine HP	85 HP	63 kW	185 HP	138 kW
Operating Speed	2,200 RPM		2,100 RPM	
Hyd. Flow	30 GPM	114 lpm	75 GPM	284 lpm
Hyd. Pressure	2,500 psi	172 bar	3,000 psi	207 bar
Length	96 in.	2,348 mm	120 in.	3,048 mm
Height	69 in.	1,753 mm	66 in.	1,676 mm
Weight	2,500 lbs	1,138 kg	5,750 lbs	2,616 kg



Distributed By:



MKT MANUFACTURING, INC.
1198 Pershall Road • St. Louis, MO 63137
phone 314.388.2254 • *fax* 314.388.1218
www.MKTPILEMAN.com