



For: Wheel Loaders

Type: Rakes

Applications: Recycling Site Prep Storm Cleanup Wood Waste Other

Loader Rakes with Paddle Clamp or Two Clamps are utilized in many applications. Recycling, land clearing and storm clean-up are probably the most common.

These rakes are designed with long teeth that are ideal for loading, piling and feeding grinders. They feature high strength and high tensile materials. These units can handle approximately 75% more material than the standard loader rake without a clamp.

The paddle clamp is essentially the two independent clamps tied together so they operate as one unit along the entire rake width.

Having two independent clamps (instead of the paddle clamp) helps when handling uneven loads, giving the opportunity for one clamp to close down tighter on the load than the other.

Please note that a third spool valve is necessary on the machine to operate the clamps or paddle.



Loader Class	Raking Width	Tine Spacing	Tine Thickness	Number of Tines	Max. Opening	Min. Opening	Weight w/o Clamps	Weight with Clamps
L-100	84"	10 7/8"	1 1/4"	8	80"	10"	1,900 lbs	2,900 lbs
L-200	96"	12"	1 1/2"	8	92"	12 1/2"	2,400 lbs	4,000 lbs
L-300	106"	13"	1 3/4"	8	95"	12 1/2"	2,900 lbs	5,085 lbs
L-500	106"	13"	1 3/4"	8	95"	12 1/2"	2,900 lbs	5,085 lbs
L-600	114"	12 1/8"	2"	9	95"	12 1/2"	3,800 lbs	6,200 lbs
L-700	122"	12 3/4"	2 1/4"	9	95"	12 1/2"	5,200 lbs	7,600 lbs
L-800	134"	14"	2 1/2"	9	98"	12 1/2"	6,900 lbs	9,800 lbs



Quality Attachments Since 1978

PEMBERTON