



BPU 3050A US

Reversible vibratory plate

Maximum compaction in the tightest spaces

The lightweight reversible vibratory plates are powerful and versatile making them ideal for base preparation, gardening, landscaping and maintenance work on streets, roads and parking lots. The Wacker Neuson vibratory plates in the 25-37 kN class come equipped with a sturdy, integrated wheel set. This unique feature provides mobility on the construction site.

Highlights

- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Technical Data

Mechanical - Output Details

•	
Centrifugal force	6,744 lbf
Area capacity	6,135.5 ft2/h
Forward Running	1.0 fps
Gradeability	36.4 %
Vibrations (Hz)	90.0 Hz
Mechanical Details	
Length Baseplate	27.7 "
Width	19.7 "
Width Baseplate	19.7 "
Height	43.3 "
Height Cover frame	29.4 "

Thickness Baseplate	0.4 "
Operating weight	366.0 lb
Ground clearance	29.4 - 33.7 "
Engine	
Effective power	7.5 hp
Nominal Engine speed	2,800.0 1/min
Environment Data	
HAV summation (average value)	9.2 ft/s2
HAV summation (Standard)	EN 500-4
Electrical System	
Coding options	0
	-

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.