



## BS68-4Ab/28

### 4-stroke Rammers

# Outstanding work performance and long service life

Wacker Neuson's 4 stroke rammers characterized by excellent work performance. The long shoe stroke, the high ramming frequency, high impact energy and fast travel speed ensure firstclass work results. Well thought-out functions make the use of the 4 stroke rammers even more operator-friendly, extend their service life, and minimize maintenance.

### Highlights

- Large stroke, high impact force
- Just one lever for starting, idling and stopping
- Efficient air filter
- Ergonomic guide handle
- Low oil warning indicator
- Large stroke, high impact force
- Efficient air filter
- Ergonomic guide handle

### **Technical Data**

Mechanical - Output Details		Stroke at tamper	2.5 "
Number of blows	689.0 1/min	Environment Data	
Area capacity	2,174.3 ft2/h	Operating temperature range	14 - 104 °F
Forward Running	0.7 fps	Sound power LWA, guaranteed	108.0 dB(A)
Power of impact	4,271.4 lbf	Sound power LWA (Standard)	EN 500-4
Mechanical Details		HAV summation (average value)	30.8 ft/s2
Length	26.1 "	HAV summation (Standard)	EN 500-4
Length Ramming Shoe	13.4 "	Electrical System	
Width	13.7 "	Display Equipment	Beacon
Width Ramming Shoe	11.0 "	Operating elements	Pushbutton OFF
Height	37.4 "	Operating Fluids	
Weight	152.34 lb	Oil specification	SAE 10W-40
Operating weight	154.3 lb	Oil volume	0.238 gal US

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.