



**WACKER
NEUSON**
all it takes!

BS68-4Ab/28

4-stroke Rammers

Outstanding work performance and long service life

Wacker Neuson's 4 stroke rammers characterized by excellent work performance. The long shoe stroke, the high ramming frequency, high impact energy and fast travel speed ensure first-class work results. Well thought-out functions make the use of the 4 stroke rammers even more operator-friendly, extend their service life, and minimize maintenance.

Highlights

- Large stroke, high impact force
- Just one lever for starting, idling and stopping
- Efficient air filter
- Ergonomic guide handle
- Low oil warning indicator
- Large stroke, high impact force
- Efficient air filter
- Ergonomic guide handle

Technical Data

■ Mechanical - Output Details

Number of blows	689.0 1/min
Area capacity	2,174.3 ft ² /h
Forward running	0.7 fps
Power of impact	4,271.4 lbf

■ Mechanical Details

Length	26.1 in
Length Ramming Shoe	13.4 in
Width	13.7 in
Width Ramming Shoe	11.0 in
Height	37.4 in
Weight	152.12 lb
Operating weight	154.3 lb

stroke at tamper 2.5 in

■ Environment Data

Operating temperature range	14 - 104 °F
Sound power LWA, guaranteed	108.0 dB(A)
Sound power LWA (Standard)	EN 500-4
HAV summation (average value)	30.8 ft/s ²
HAV summation (Standard)	EN 500-4

■ Electrical System

Display Equipment	Beacon
Operating elements	Pushbutton OFF

■ Operating Fluids

Oil specification	SAE 10W-40
Oil volume	0.238 gal US

■ Honda GXR120RT-KR-W1-SD

Cylinder capacity	7.4 Inch ³
Fuel consumption	0.3 GPH US
Tank capacity	0.8 gal US
Effective power	3.1 PS
Operating power	3.6 PS
Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1
Kraftstofftyp	Gasoline
Standard (Effective power)	SAE J1349
Standard (Operating power)	ISO 3046-1
Starter type	Recoil starter
Engine Manufacturer	Honda
Engine Designation	GXR120RT-KR-W1-SD