

## MSD Saber and Saber Lube Specifications

Model	Excavator Weight 2nd Member		Excavator Weight 3rd Member		Attachment Weight		Jaw Opening		Jaw Depth		Reach (2nd member)	
	Lbs.	M Tons	Lbs.	M Tons	Lbs.	Kg.	in.	mm	ft.	mm	ft.	M
<b>MSD 1000</b>	20,000	9	35,000	16	4,200	1,910	19	482	20	508	5'11"	1.8
<b>MSD 1000R</b>	23,000	10	40,000	18	4,400	2,000	19	482	20	508	8'6"	2.5
<b>MSD 1500</b>	27,000	12	55,000	25	6,600	3,000	22	559	25	635	6'9"	2.1
<b>MSD 1500R</b>	40,000	18	66,000	30	7,000	3,180	22	559	25	635	9'3"	2.8
<b>MSD 2000</b>	42,000	19	70,000	32	8,850	4,020	28	711	29	737	8'3"	2.5
<b>MSD 2000R</b>	50,000	23	90,000	41	10,200	4,636	28	711	29	737	11'0"	3.4
<b>MSD 2000-SL</b>	42,000	19	70,000	32	9,050	4,110	28	711	29	737	8'3"	2.5
<b>MSD 2000R-SL</b>	50,000	23	90,000	41	10,400	4,727	28	711	29	737	11'8"	3.5
<b>MSD 2500</b>	50,000	23	90,000	41	12,000	5,450	32	813	34	864	8'9"	2.7
<b>MSD 2500R</b>	70,000	32	110,000	50	14,600	6,640	32	813	34	864	12'6"	3.8
<b>MSD 2500-SL</b>	50,000	23	90,000	41	12,000	5,450	32	813	34	864	8'9"	2.7
<b>MSD 2500R-SL</b>	70,000	32	110,000	50	14,800	6,730	32	813	34	864	12'6"	3.8
<b>MSD 3000</b>	70,000	32	144,000	65	13,300	6,045	35	889	38	965	9'10"	3.0
<b>MSD 3000R</b>	95,000	43	160,000	73	17,000	7,730	35	889	38	965	14'1"	4.3
<b>MSD 3000-SL</b>	70,000	32	144,000	65	13,500	6,140	35	889	38	965	9'10"	3.0
<b>MSD 3000R-SL</b>	95,000	43	160,000	73	17,200	7,820	35	889	38	965	14'1"	4.3
<b>MSD 4500</b>	90,000	41	160,000	73	17,900	8,140	38.5	978	43	1,092	10'8"	3.3
<b>MSD 4500R</b>	110,000	50	185,000	84	21,000	9,545	38.5	978	43	1,092	14'2"	4.3
<b>MSD 4500-SL</b>	90,000	41	160,000	73	18,100	8,230	38.5	978	43	1,092	10'8"	3.3
<b>MSD 4500R-SL</b>	110,000	50	185,000	84	21,200	9,640	38.5	978	43	1,092	14'2"	4.3
<b>MSD 7500</b>	135,000	61	consult factory		25,500	11,590	43	1092	45	1,143	11'10"	3.6
<b>MSD 7500R</b>	160,000	73	275,000	125	30,000	13,640	43	1092	45	1,143	15'7"	4.7
<b>MSD 7500-SL</b>	135,000	61	consult factory		25,700	11,680	43	1092	45	1,143	11'10"	3.6
<b>MSD 7500R-SL</b>	160,000	73	275,000	125	30,200	13,730	43	1092	45	1,143	15'7"	4.7
<b>MSD 9500</b>	175,000	80	consult factory		37,300	16,950	48	1219	52	1,321	15'4"	4.6
<b>MSD 9500R</b>	275,000	125	consult factory		43,300	19,680	48	1219	52	1,321	18'4"	5.6
<b>MSD 9500-SL</b>	175,000	80	consult factory		37,500	17,050	48	1219	52	1,321	15'4"	4.6
<b>MSD 9500R-SL</b>	275,000	125	consult factory		44,500	20,230	48	1219	52	1,321	18'4"	5.6

**Note:** Actual weights will vary, depending up options chosen, excavator bracket requirements, etc. All applications must be approved by Stanley Labounty Applications Engineering.